

## ROMOVER 59.08 Wagon Mover

For moving wagons of up to 60 t total weight.

- To be used on level surfaces
- For flat bottom and grooved rails as well as on slab track
- Recommended wheel diameter 600 to 1000 mm
- Dimensions (L x W x H) 2500 x 190 x 140 mm
- Double cropped version for very short stroke available, wagon mover can be applied slanted
- Weight from 12 kg



## ROCHOCK 59.09 Wheel Chock

Press-on wheel chock

### THE ADVANTAGES. YOUR BENEFITS.

#### Simple design

- Makes coupling process easier by preventing long-coupled wagon formations from decoupling in departure tracks
- Press-on wheel chock will fall off the rail without affecting the clearance gauge thanks to its eccentrically arranged counter-weight

#### Versions

- 9805909002 Right-hand version press-on wheel chock  
9805909003 Left-hand version press-on wheel chock



Wheel Chock L130

### THE ADVANTAGES. YOUR BENEFITS.

#### Simple design

- Secures stationary wagons from unintended movement
- After bolting the chock to the rail head and removing the split pin, the key can be removed, securing the chock against unauthorised removal

#### Versions

- 9891053208 Wheel chock, both sides  
Can be locked with removable key.  
Total length 640 mm  
Tip length per wedge ramp 160 mm
- 9805909011 Wheel chock, both sides  
Can be locked with removable key.  
Total length 740 mm  
Tip length per wedge ramp 210 mm  
Particularly suited for inclines.



## Wheel Chock L134

### THE ADVANTAGES. YOUR BENEFITS.

#### Simple design

- Was developed for securing stationary freight wagons
- Available for wheel diameters 810 – 1000 mm as well as 630 – 760 mm

#### Versions

- 9805909001 Wheel chock L134  
9805910003 Wheel chock L134S

With long bracket for easier application.



## ROSTOP 59.10 Drag Shoe

### For dragging slowly rolling vehicles.

- Standard drag shoe of DB
- Double fishplated for flat bottom rails
- Single fishplated for grooved rails (left-hand and right-hand side)
- Cap and handle replaceable
- Dimensions (L x W x H) 550 x 90 x 140 mm
- Weight from 7.5 kg

Various versions on request.



## RODERAIL 59.11 Double Drag Shoe

### For dragging slowly rolling vehicles.

- Consists of 2 double fishplated standard DB drag shoes
- Connected by a thread rod and a steel tube
- Cap and handle replaceable
- Weight from 20 kg

Various versions on request.

