

**ROMEAS****83.07 RCA****Switch Gauge and Superelevation Measuring Device**

For all common measuring points of switches.

**THE ADVANTAGES. YOUR BENEFITS.****Light. Easy to handle. Modular.**

- Modular design and low weight
- Available for different track gauges
- Insulated from rail to rail
- Individual functions can be extended with equipment options
- DB user acceptance

**SPECIFICATION**

Track gauge	1435 mm (1415 mm to 1475 mm)
Check rail gauge	1385 mm to 1405 mm
Back to back distance	1345 mm to 1361 mm
Flange groove	30 mm to 82 mm
Cross level	-30 mm to +200 mm
Weight	2.5 kg

**ACCESSORIES**

Changeover bolt  
 Fibre glass version (fully insulated)  
 Segmented version for track gauge  $\geq 1435$  mm  
 Version for grooved rails  $\geq 20$  mm  
 Test adapter for switch blades (gauges 1/2)  
 DB test adapter for switch blades (gauges 1/2/2-19/2-21)

Measuring device for frog nose incline  
 Grooved rail adjustment  
 Check rail level measuring device  
 Transport bag for segmented devices  
 Transport and storage case

**ROMEAS****83.15 POINT****Fixed Point Measuring Device**

For measuring distances between fixed points at the track and signal posts, concrete walls, etc. and for checking individual level values using an appropriate measuring staff.

**THE ADVANTAGES. YOUR BENEFITS.**

- Attached to the rail by magnets
- Exact position adjustable via a level

**SPECIFICATION**

Weight	1.2 kg
--------	--------

